

## Light Shadow Surface Dali Version 4 Spots Optic Wide Flood

Designed by FLOS Architectural




LED - Power LED - 10.8W - 1022lm - 2700K - CRI> 90 - Beam° 45

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1192                |
| Lumen Output (lm)      | 1022                |
| Efficacy (lm/W)        | 94                  |

### Physical

|                 |                   |
|-----------------|-------------------|
| Colour          | White/White/White |
| Trim            | No                |
| Orientation     | Fixed             |
| Length (mm)     | 146               |
| Net weight (kg) | 0.8               |
| IP internal     | 44                |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 45        |
| Beam angle C90-270 (°) | 44        |
| Extreme cut off        | No        |
| UGRL                   | <16       |

Electrical

|                    |                 |
|--------------------|-----------------|
| Insulation class   | I               |
| Frequency (Hz)     | 50/60           |
| Main voltage (Vac) | 220-240         |
| Power supply       | Integrated      |
| Dimmable           | Yes             |
| Power supply type  | Dimmable DALI 1 |
| Emergency          | No              |