


Light Shadow Surface Mains Dimming Version 4 Spots Square Optic Wide Flood

Designed by FLOS Architectural, 2022



836lm - 3000K - CRI> 90 - Beam° 49

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	9
Source flux (lm)	1281
Lumen Output (lm)	836
Efficacy (lm/W)	92

Physical

Colour	Black/Black/White
Orientation	Fixed
Net weight (kg)	0.6
Package height (mm)	19
Package width (mm)	18
Package length (mm)	22
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	49
Beam angle C90-270 (°)	49
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	700
Power supply	Integrated
Dimmable	Yes
Power supply type	Mains Cut Dimming