

## Light Shadow Wall-Washer 0-10V Dimmable

Designed by FLOS Architectural, 2018



10.8W - 2700K - CRI> 90

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| System power (W)       | 0                   |
| Source flux (lm)       | 0                   |

### Physical

|                     |         |
|---------------------|---------|
| Color               | Black   |
| Net weight (lb)     | 0.75    |
| Gross weight (lb)   | 1.02    |
| Package height (in) | #VALUE! |
| Package width (in)  | #VALUE! |
| Package length (in) | #VALUE! |
| Package volume (in) | 62      |
| IP internal         | 20      |
| IP external         | 20      |



### Download

Family spec sheet [ZIP](#)  
Mounting instructions [PDF](#)

### Photometric Files

LDT / IES [ZIP](#)

### Technical Drawings


2D [ZIP](#)  
3D [ZIP](#)



### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Light distribution | Asymmetric |
| CCT (K)            | 2700       |
| CRI>               | 90         |
| Extreme cut off    | No         |

Electrical

|                     |                |
|---------------------|----------------|
| Insulation class    | II             |
| Forward voltage (V) | 24             |
| LED current (mA)    | 900            |
| Dimmable            | Yes            |
| Dimming type        | Dimmable 0-10V |