

# FLOS

03.9905.14CDA Black

## Light Shadow Wall-Washer DALI Version

Designed by FLOS Architectural, 2018



LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.8
System power (W)	0
Source flux (lm)	0

### Physical

Colour	Black
Trim	No
Orientation	Fixed
Length (mm)	140
Net weight (kg)	0.34
IP internal	20



### Download

[Mounting instructions](#) PDF

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings

[2D](#) ZIP


[3D](#) ZIP



### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

## Schematic light drawing



Beam Angle:	24°		
h(m)	E(lx)	D(m)	
1	1029	0.54	
2	257	1.08	
3	114	1.62	
4	64	2.16	
5	41	2.70	

## Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	92
Rg gamut index	100
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Extreme cut off	No

## Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	1-100

## Notes

For wireless lighting control, choose integrated Casambi versions.