

Light Shadow Wall-Washer DALI Version

Designed by FLOS Architectural, 2018



LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.8
System power (W)	0
Source flux (lm)	0

Physical

Color	White
Trim	No
Orientation	Fixed
Length (in)	5.51
Net weight (lb)	0.74
IP internal	20



Download

- [Family spec sheet](#)  ZIP
- [Mounting instructions](#)  PDF

Photometric Files

- [LDT / IES](#)  ZIP

Technical Drawings


- [2D](#)  ZIP
- [3D](#)  ZIP



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	92
Rg gamut index	100
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	1-100

Notes

For wireless lighting control, choose integrated Casambi versions.