

FLOS

05.5194.14.DA Black

Light Stripe 1200 Dali Dimmable

Designed by FLOS Architectural, 2023


13.5W - 777lm - 2700K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	13.5
Source flux (lm)	1667
Lumen Output (lm)	777
Efficacy (lm/W)	58

Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	0.09
IP internal	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings

2D  ZIP

3D  ZIP




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Beam Angle:	115°		
h(m)	E(lx)	D(m)	
1	261	3.15	
2	65	6.29	
3	29	9.44	
4	16	12.59	
5	10	15.73	

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	700
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)