

03.7006.14B90 Black

Light Stripe 1200 mm

Designed by FLOS Architectural, 2017




30W - 1665lm - 2700K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	30
Source flux (lm)	2600
System flux (lm)	1665

Physical

Color	Black
Length (in)	47.24
Net weight (lb)	3
Gross weight (lb)	3.6
Package height (in)	#VALUE!
Package width (in)	#VALUE!
Package length (in)	#VALUE!
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
Dimmable	Yes
Dimming type	Non Dimmable