

FLOS

03.7007.14B Black

Light Stripe 1200 mm

Designed by FLOS Architectural, 2017



LED - Top LED - 30W - 1760lm - 3000K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	30
System power (W)	32.4
Source flux (lm)	1779
Lumen Output (lm)	1760
Efficacy (lm/W)	54.32

Physical

Colour	Black
Trim	No
Orientation	Fixed
Length (mm)	1206
Net weight (kg)	1.36
IP internal	20
IP external	20

Download

Mounting instructions  PDF

Photometric Files


LDT / IES  ZIP

Technical Drawings

2D  ZIP
3D  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable

Notes