

Light Stripe 1200 mm Dimmable DALI

Designed by FLOS Architectural



LED - Top LED - 30W - 1665lm - 2700K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	30
System power (W)	32.4
Source flux (lm)	1706
Lumen Output (lm)	1665
Efficacy (lm/W)	51.39

Physical

Colour	Black
Trim	No
Orientation	Fixed
Length (mm)	1206
Net weight (kg)	1.36
IP internal	20
IP external	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	10-100

Notes