

# FLOS

05.5195.14 Black

## Light Stripe 1200 Non Dimmable


Designed by FLOS Architectural, 2023

13.5W - 816lm - 3000K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	13.5
Source flux (lm)	1750
Lumen Output (lm)	816
Efficacy (lm/W)	61

### Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	0.09
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113

### Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	700
Power supply	Remote excluded
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)