

Light Stripe 1200 Recessed Profile 1-10V Dimmable

Designed by FLOS Architectural, 2024




13.5W - 777lm - 2700K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro recessed system.
Electronic DC/DC converter incorporated. Broadcast control via 1-10V protocol.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	13.5
System power (W)	13.5
Source flux (lm)	1667
System flux (lm)	777

Physical

Color	Black
Field cuttable	No
IP internal	20

Download

- Family spec sheet  ZIP
- Mounting instructions  PDF

Photometric Files


- LDT / IES  ZIP

Technical Drawings

- 2D  ZIP
- 3D  ZIP




Schematic light drawing



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Non-replaceable light source

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	96
LED Life / Failure Ratio	L90B10=100.000h (Tc=70°C=
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	700
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No