

Light Stripe 1200 Recessed Profile Non Dimmable


Designed by FLOS Architectural, 2024

13.5W - 816lm - 3000K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro recessed system.
Electronic DC/DC converter incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	13.5
System power (W)	13.5
Source flux (lm)	1750
System flux (lm)	816

Physical

Color	Black
Field cuttable	No
IP internal	20

Download

- Family spec sheet

ZIP
- Mounting instructions

PDF

Photometric Files

- LDT / IES

ZIP

Technical Drawings

- 2D


ZIP
- 3D

ZIP




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	97
LED Life / Failure Ratio	L90B10=100.000h (Tc=70°C=
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	700
Driver	Remote
Dimmable	No
Dimming type	Non Dimmable
Batteries inside	No