

FLOS

03.7000.14B9V Black

Light Stripe 300 mm 0-10V Dimmable

Designed by FLOS Architectural, 2017



7.5W - 416lm - 2700K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	7.5
Source flux (lm)	650
System flux (lm)	416

Physical

Color	Black
Length (in)	11.81
Net weight (lb)	0.75
Gross weight (lb)	0.9
Package volume (in)	123
IP internal	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
LED current (mA)	300
Dimmable	Yes
Dimming type	Dimmable 0-10V

Notes