

# FLOS

03.7000.14B90 Black

## Light Stripe 300 mm

Designed by FLOS Architectural, 2017



621lm - 2700K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Number of lamps        | 1                   |
| System power (W)       | 7.4                 |
| Source flux (lm)       | 868                 |
| System flux (lm)       | 621                 |
| Efficacy (lm/W)        | 84                  |

### Physical

|                     |         |
|---------------------|---------|
| Color               | Black   |
| Length (in)         | 11.81   |
| Net weight (lb)     | 0.75    |
| Gross weight (lb)   | 0.9     |
| Package height (in) | #VALUE! |
| Package width (in)  | #VALUE! |
| Package length (in) | #VALUE! |
| IP internal         | 20      |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files


LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)  
3D [↓ ZIP](#)



Schematic light drawing



Photometric

|                        |            |
|------------------------|------------|
| Light distribution     | Asymmetric |
| CCT (K)                | 2700       |
| CRI>                   | 90         |
| Beam angle C0-180 (°)  | 108        |
| Beam angle C90-270 (°) | 105        |
| Extreme cut off        | No         |

Electrical

|                     |              |
|---------------------|--------------|
| Insulation class    | II           |
| Forward voltage (V) | 24           |
| Dimmable            | Yes          |
| Dimming type        | Non Dimmable |