

FLOS

03.7002.14.9V Black

Light Stripe 600 mm 0-10V Dimmable


Designed by FLOS Architectural, 2017



Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	15
Source flux (lm)	1300
System flux (lm)	833

Physical

Color	Black
Length (in)	23.62
Net weight (lb)	1.5
Gross weight (lb)	1.81
Package volume (in)	306
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
LED current (mA)	625
Dimmable	Yes
Dimming type	Dimmable 0-10V

Notes

Class 2.