


FLOS

03.7003.14.9V Black


Light Stripe 600 mm 0-10V Dimmable

Designed by FLOS Architectural, 2017



1259lm - 3000K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
System power (W)	14.8
Source flux (lm)	1760
Lumen Output (lm)	1259
Efficacy (lm/W)	86

Physical

Colour	Black
Length (mm)	600
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
Dimmable	Yes
Power supply type	Dimmable 0-10V

Notes

Class 2.

