

Light Stripe 600 mm Dimmable 1-10V


Designed by FLOS Architectural, 2017



Diffused LED light module to be installed in The Tracking Magnet System.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 12                  |
| Source flux (lm)       | 1372                |
| Lumen Output (lm)      | 520                 |
| Efficacy (lm/W)        | 43                  |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Trim            | No    |
| Orientation     | Fixed |
| Length (mm)     | 600   |
| Net weight (kg) | 0.21  |
| IP internal     | 20    |
| IP external     | 20    |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP

### Technical Drawings


2D  ZIP

3D  ZIP




### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Photometric

|                          |                            |
|--------------------------|----------------------------|
| Lighting type            | Direct                     |
| Light distribution       | Symmetric                  |
| CCT (K)                  | 2700                       |
| CRI>                     | 80                         |
| McAdam steps (SDCM)      | 2                          |
| LED Life / Failure Ratio | L80B50 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 109                        |
| Beam angle C90-270 (°)   | 109                        |
| Extreme cut off          | No                         |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 48                                    |
| LED current (mA)    | 250                                   |
| Power supply        | Remote excluded                       |
| Dimmable            | Yes                                   |
| Power supply type   | Dimmable 1-10V                        |
| Dimming range (%)   | 20-100                                |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Emergency           | No                                    |

Notes

Opal end covers not included. They must be ordered separately (08.0125.00 includes two units). Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.

Accessories & Power Supply



OPTIONAL  
Accessory

08.0125.00

Opal End Caps for Tracking  
Magnet Light Stripe. 2 unit kit