

FLOS

03.7003.14BDD Black

Light Stripe 600 mm Dimmable DALI

Designed by FLOS Architectural, 2017



1259lm - 3000K - CRI> 90 - Beam° 108

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
System power (W)	14.8
Source flux (lm)	1760
System flux (lm)	1259
Efficacy (lm/W)	86

Physical

Color	Black
Length (in)	23.62
Net weight (lb)	1.5
Gross weight (lb)	1.81
Package volume (in)	306
IP internal	20

Download

Mounting instructions



PDF

Photometric Files

LDT / IES



ZIP

Technical Drawings

2D



ZIP


3D



ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
Dimmable	Yes
Dimming type	Dimmable DALI 2

Notes