

Light Stripe 900 1-10V Dimmable


Designed by FLOS Architectural, 2023

10W - 518lm - 2700K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Number of lamps        | 1                   |
| Power (W)              | 10                  |
| Source flux (lm)       | 1111                |
| System flux (lm)       | 518                 |
| Efficacy (lm/W)        | 52                  |

## Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Orientation | Fixed |
| IP internal | 20    |

## Download

- Family spec sheet
- Mounting instructions
- ZIP
- PDF

## Photometric Files

- LDT / IES
- ZIP

## Technical Drawings

- 2D
- 3D
- ZIP
- ZIP




## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| Light distribution     | Asymmetric |
| CCT (K)                | 2700       |
| CRI>                   | 90         |
| McAdam steps (SDCM)    | 3          |
| Beam angle C0-180 (°)  | 115        |
| Beam angle C90-270 (°) | 113        |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| LED current (mA)    | 500                                   |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable 1-10V                        |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |