

FLOS

03.7004.14.9V Black

Light Stripe 900 mm 0-10V Dimmable


Designed by FLOS Architectural, 2017



Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	22.5
Source flux (lm)	1950
System flux (lm)	1249

Physical

Color	Black
Length (in)	35.43
Net weight (lb)	2.25
Gross weight (lb)	2.71
Package volume (in)	428
IP internal	20

Download

Family spec sheet	↓ ZIP
Mounting instructions	↓ PDF

Photometric Files


LDT / IES	↓ ZIP
-----------	-------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 > 60.000h (Tc=55°C)
Beam angle C0-180 (°)	108
Beam angle C90-270 (°)	105
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
Dimmable	Yes
Dimming type	Dimmable 0-10V

Notes

Class 2.