

FLOS

05.5192.14 Black

Light Stripe 900 Non Dimmable

Designed by FLOS Architectural, 2023




10W - 518lm - 2700K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	10
Source flux (lm)	1111
Lumen Output (lm)	518
Efficacy (lm/W)	52

Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	0.06
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Schematic light drawing



Beam Angle: 115°

h(m)	E(lx)	D(m)
1	174	3.15
2	43	6.29
3	19	9.44
4	11	12.59
5	7	15.73

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	500
Power supply	Remote excluded
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)