

Light Stripe 900 Non Dimmable

Designed by FLOS Architectural, 2023




10W - 518lm - 2700K - CRI> 90 - Beam° 115

LED diffuse lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	10
Source flux (lm)	1111
System flux (lm)	518
Efficacy (lm/W)	52

Physical

Color	Black
Orientation	Fixed
IP internal	20

Download

- Family spec sheet  ZIP
- Mounting instructions  PDF

Photometric Files

- LDT / IES  ZIP

Technical Drawings


- 2D  ZIP
- 3D  ZIP



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Beam angle C0-180 (°)	115
Beam angle C90-270 (°)	113

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	500
Driver	Remote excluded
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)