

FLOS

03.2268.14 Black

Light Stripe Diffused

Designed by FLOS Architectural, 2020




LED - Top LED - 13.5W - 616lm - 2700K - CRI> 90 - Beam° 114

Diffused LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 13.5 |
| System power (W) | 17 |
| Source flux (lm) | 616 |
| Lumen Output (lm) | 616 |
| Efficacy (lm/W) | 36.24 |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Orientation | Fixed |
| Length (mm) | 900 |
| Net weight (kg) | 0.09 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Beam Angle: 114°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 172 | 3.11 |
| 2 | 43 | 6.21 |
| 3 | 19 | 9.32 |
| 4 | 11 | 12.43 |
| 5 | 7 | 15.53 |

Photometric

| | |
|--------------------------|---------------------------|
| Lighting type | Direct |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 2 |
| LED Life / Failure Ratio | L90B10>100.000h (Tc=71°C) |
| Beam angle C0-180 (°) | 114 |
| Beam angle C90-270 (°) | 135 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Non Dimmable, Dimmable |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |