

FLOS

03.2282.14 Black

Light Stripe Wall-Washer

Designed by FLOS Architectural, 2020




LED - Top LED - 4.5W - 213lm - 4000K - CRI> 90 - Beam° 114

Asymmetric wall-washer LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 4.5 |
| System power (W) | 5 |
| Source flux (lm) | 213 |
| Lumen Output (lm) | 213 |
| Efficacy (lm/W) | 42.6 |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Orientation | Fixed |
| Length (mm) | 300 |
| Net weight (kg) | 0.09 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)

Ecodesign and Energy


Labelling

 Replaceable (LED only) light source by a professional

 ↔ 



Schematic light drawing



Beam Angle:

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 3 | |
| 2 | 5 | |
| 3 | 12 | |
| 4 | 48 | |
| 5 | 0 | |

Photometric

| | |
|--------------------------|---------------------------|
| Lighting type | Direct |
| Light distribution | Asymmetric |
| CCT (K) | 4000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 2 |
| LED Life / Failure Ratio | L90B10>100.000h (Tc=71°C) |
| Beam angle C0-180 (°) | 114 |
| Beam angle C90-270 (°) | 135 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Non Dimmable, Dimmable |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |