

# FLOS

03.2287.14 Black

## Light Stripe Wall-Washer

Designed by FLOS Architectural, 2020




LED - Top LED - 9W - 408lm - 5000K - CRI> 90 - Beam° 114

Asymmetric wall-washer LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	9
System power (W)	11
Source flux (lm)	408
Lumen Output (lm)	408
Efficacy (lm/W)	37.09

### Physical

Colour	Black
Orientation	Fixed
Length (mm)	600
Net weight (kg)	0.09
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files


LDT / IES [↓ ZIP](#)

### Technical Drawings

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)

### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional



## Schematic light drawing



Beam Angle:

h(m)	E(lx)	D(m)
1	6	
2	10	
3	23	
4	92	
5	0	

Luminous flux luminaire  
408 lm

## Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	5000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L90B10>100.000h (Tc=71°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135

## Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)