

Light Stripe Wall-Washer Broadcast

Designed by FLOS Architectural, 2026



LED - Top LED - 18W - 853lm - 4000K - CRI> 90 - Beam° 114

LED lighting module with asymmetric wall-washer light distribution for installation in the The Micro Running Magnet Pro system. Broadcast version, with simultaneous control of all luminaires.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	18
System power (W)	23.5
Source flux (lm)	853
Lumen Output (lm)	853
Efficacy (lm/W)	36.3

Physical

Colour	Black
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	0.09
IP internal	20

Drawing Thumbnail

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings

2D  ZIP


3D  ZIP

Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L90B10>100.000h (Tc=71°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)