

Light Supply Wall-Washer Trim

Designed by FLOS Architectural, 2017

LED - LED array - 33.2W - 2142lm - 3000K - CRI> 80 - Beam° 36

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	33.2
Source flux (lm)	3959
Lumen Output (lm)	2142

Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	51

Electrical

Insulation class	II
Frequency (Hz)	50/60
Forward voltage (V)	37
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable
Emergency	No