

Light Supply Wall-Washer Trim Dimmable

Designed by FLOS Architectural, 2017

LED - LED array - 33.2W - 2142lm - 3000K - CRI> 80 - Beam° 36

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	33.2
Source flux (lm)	3959
Lumen Output (lm)	2142

Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44



Photometric Files


LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)
3D [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	51
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable 1-10V