

03.8107.14A Black

Light Tube Ø 30 Direct 1500 mm On Board Dimmer

Designed by Vincent Van Duysen




38W - 3000K - CRI> 90 - Beam° 150

Diffused LED light module to be installed in The Infra-Structure.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	38

Physical

Color	Black
Orientation	Fixed
Length (in)	60.79
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	150
Beam angle C90-270 (°)	106

Electrical

Insulation class	III
Forward voltage (V)	48
Driver	Remote
Dimmable	Yes
Dimming type	Dimmer on board
Dimming interface	Dimmer Integrated

Notes

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.