

FLOS

03.8115.14ADA Black

Light Tube Ø 30 Indirect 900 mm Dali Version


Designed by Vincent Van Duysen



Diffused LED light module to be installed in The Infra-Structure.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Number of lamps | 1 |
| Power (W) | 23 |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Orientation | Fixed |
| Length (mm) | 944 |
| Net weight (kg) | 0.8 |
| Package volume (m3) | 0.03 |
| IP internal | 20 |

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 558 | 2.10 |
| 2 | 139 | 4.20 |
| 3 | 62 | 6.30 |
| 4 | 35 | 8.40 |
| 5 | 22 | 10.51 |

Photometric


| | |
|------------------------|-----------|
| Lighting type | Indirect |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 93 |
| Beam angle C90-270 (°) | 102 |
| UGR _L | <10 |

Electrical


| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Forward voltage (V) | 48 |
| Power supply | Remote |
| Dimmable | Yes |
| Power supply type | Dimmable DALI 2 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy

Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.