FLOS

03.8110.40A White

Light Tube Ø 30 Indirect 900 mm On Board Dimmer

Designed by Vincent Van Duysen

Diffused LED light module to be installed in The Infra-Structure.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	23

Physical

Colour	White
Orientation	Fixed
Length (mm)	944
Net weight (kg)	0.8
Package volume (m3)	0.03
IP internal	20

RG IEC 62471

GWT 850°

IP 20

Download

Mounting instructions PDF

Photometric Files

LDT / IES ZIP

Technical Drawings

2D ZIP

3D ZIP

Bim ZIP

Schematic light drawing



Luminous flux luminaire
1260 lm

Beam Angle: 93°

h(m)	E(lx)	D(m)
1	541	2.10
2	135	4.20
3	60	6.30
4	34	8.40
5	22	10.51

©2026 Flos - P.IVA 00290820174 - 5/30/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Photometric

Lighting type	Indirect
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	93
Beam angle C90-270 (°)	102
UGR_L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Dimmer Integrated

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.

©2026 Flos - P.IVA 00290820174 - 5/30/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.