

# FLOS

06.0456.14 Black

## Live end Feed

Designed by FLOS Architectural, 2024




Track

Power supply unit for the remote power source unit. Includes preinstalled power cable and is compatible with both on/off and dimmable versions.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light sources included	No

### Physical

Colour	Black
Field cuttable	No
Net weight (kg)	0.2
IP internal	20

### Download

[Mounting instructions](#)




## Photometric

Extreme cut off No

## Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable DALI 2, Dimmable 1-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.

REQUIRED  
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V, 24/48V. For remote installation.

REQUIRED  
Power supply

Electrical

60.9777A

Remote Power Supply Non Dimmable 24V. 120W. 220/240V

REQUIRED  
Power supply

Electrical

60.9705A

Remote Power Supply Non Dimmable 24V. 60W. 220/240V