

## Live end Feed

Designed by FLOS Architectural, 2024



Track

Power supply unit for the remote power source unit. Includes preinstalled power cable and is compatible with both on/off and dimmable versions.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light sources included | No                  |

### Physical

|                |       |
|----------------|-------|
| Color          | Black |
| Field cuttable | No    |
| IP internal    | 20    |



### Download

- Family spec sheet
- Mounting instructions
- ZIP
- PDF




Photometric

Extreme cut off                      No

Electrical

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Insulation class    | III                                                 |
| Forward voltage (V) | 24                                                  |
| Driver              | Remote                                              |
| Dimmable            | Yes                                                 |
| Dimming type        | Non Dimmable,<br>Dimmable DALI 2,<br>Dimmable 1-10V |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not<br>Included)         |
| Batteries inside    | No                                                  |

Accessories & Power Supply



REQUIRED  
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V,  
24/48V. For remote installation.