

Magic Stick 145 Asymmetric Dali Dimmable


Designed by Jorge Herrera, 2023

9.8W - 823lm - 2700K - CRI> 90 - Beam° 133

LED diffuse and accent lighting module for installation in the Zero Track Pro system.
Can be adjusted by rotating from its axis located in an asymmetrical position.
Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	9.8
System power (W)	11.4
Source flux (lm)	1433
Lumen Output (lm)	823
Efficacy (lm/W)	72

Physical

Colour	Black
Rotation (°)	360
Net weight (kg)	0.49
IP internal	20

Download

Mounting instructions

PDF

Photometric Files

LDT / IES

ZIP

Technical Drawings

2D


ZIP

3D

ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	96
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	133
Beam angle C90-270 (°)	112
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	750
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

The specified angle refers to the section of the luminaire with diffuse linear lighting. The corresponding beam angle for the Spots is 17°.