FLOS

05.3230.14BDA Black


Magic Stick 145 Asymmetric Dali Dimmable

Designed by Jorge Herrera, 2023



9.8W - 823lm - 2700K - CRI> 90 - Beam° 133

LED diffuse and accent lighting module for installation in the Zero Track Pro system. Can be adjusted by rotating from its axis located in an asymmetrical position. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	9.8
System power (W)	11.4
Source flux (lm)	1433
System flux (lm)	823
Efficacy (lm/W)	72

Physical

Color	Black
Rotation (°)	360
IP internal	20

Download

Family spec sheet ZIP

Mounting instructions PDF

Photometric Files

LDT / IES ZIP

Technical Drawings

2D ZIP


3D ZIP

UK CA | RG IEC 62471 | EAC | CE | IP 20

©2026 Flos - P.IVA 00290820174 - 11/1/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing




Luminous flux luminaire
673 lm

Beam Angle: - 112°


h(m)	E(lx)	D(m)
1	170	4.65
2	42	9.29
3	19	13.94
4	11	18.59
5	7	23.24

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	96
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	133
Beam angle C90-270 (°)	112
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	750
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

The specified angle refers to the section of the luminaire with diffuse linear lighting. The corresponding beam angle for the Spots is 17°.

©2026 Flos - P.IVA 00290820174 - 11/1/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.