

Magic Stick 145 Non Dimmable


Designed by Jorge Herrera, 2023

9.8W - 687lm - 3000K - CRI> 90 - Beam° 133

LED diffuse lighting module for installation in the Zero Track Pro system. Can be adjusted by rotating from its central line. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	9.8
System power (W)	9.2
Source flux (lm)	1200
Lumen Output (lm)	687
Efficacy (lm/W)	75

Physical

Colour	Black
Rotation (°)	360
Net weight (kg)	0.26
IP internal	20

Download

Mounting instructions PDF

Photometric Files

LDT / IES ZIP


Technical Drawings

2D ZIP

3D ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	97
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	133
Beam angle C90-270 (°)	112
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	750
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional