

## Micro Spot Adressable

Designed by FLOS Architectural, 2026



LED - Power LED - 3W - 231lm - 4000K - CRI> 90 - Beam° 28

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic converter. "Addressable" version, with individual control of up to 3 addresses or groups.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 3                   |
| System power (W)       | 3                   |
| Source flux (lm)       | 315                 |
| Lumen Output (lm)      | 231                 |
| Efficacy (lm/W)        | 77                  |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Black      |
| Orientation              | Adjustable |
| Rotation (°)             | 267        |
| Longitudinal tilting (°) | 90         |
| Spot diameter (mm)       | 24         |
| Length (mm)              | 41         |
| Net weight (kg)          | 0.03       |
| IP internal              | 20         |

Drawing Thumbnail

### Download

Mounting instructions PDF

### Photometric Files

LDT / IES ZIP

### Technical Drawings

2D ZIP


3D ZIP

### Ecodesign and Energy Labelling

Replaceable (LED only)  
light source by a  
professional



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 28        |
| Beam angle C90-270 (°) | 28        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <16       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| Power supply        | Remote excluded                       |
| Dimmable            | Yes                                   |
| Power supply type   | Non Dimmable, Dimmable                |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Accessories & Power Supply



REQUIRED  
Accessory

Optical

08.0190.14

Honeycomb for Micro Spot