

FLOS

■ F030B43A030 Black

Mile Recessed 1

Designed by Antonio Citterio, 2020

755lm - 4000K - CRI> 80 - Beam° 40



LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with neoprene cable outlet and double cable grommet for in/out connection. Ceiling mounting springs included. Box for brick roofing installation to be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|----------------------|
| EAN | 8054793551142 |
| Mounting | Ceiling recessed |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| System power (W) | 11 |
| Lumen Output (lm) | 755 |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Orientation | Fixed |
| Net weight (kg) | 0.87 |
| Package height (mm) | 97 |
| Package width (mm) | 221 |
| Package length (mm) | 124 |
| IP internal | 66 |

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Beam Angle: 39°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1881 | 0.71 |
| 2 | 470 | 1.42 |
| 3 | 209 | 2.14 |
| 4 | 118 | 2.85 |
| 5 | 75 | 3.56 |

Luminous flux luminaire
755 lm

Photometric


| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 40 |
| Beam angle C90-270 (°) | 40 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Accessories & Power Supply



OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68
H2O stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL Accessory

F030Z010000

Metal installation box for
concrete ceiling