

# FLOS

F015D33A033 Anthracite

## Mile Wall 2 Asymmetric Up & Down

Designed by Antonio Citterio, 2020



8W - 1254lm - 3000K - CRI> 80

LED light source included. Integrated 220-240V ON/OFF and 1-10V or DALI dimmable electrical power. Equipped with double cable gland for electrical connection.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793228105 |
| Mounting               | Wall          |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| Power (W)              | 8             |
| System power (W)       | 7.8           |
| Lumen Output (lm)      | 1254          |

### Physical

|                     |            |
|---------------------|------------|
| Colour              | Anthracite |
| Orientation         | Fixed      |
| Net weight (kg)     | 1.08       |
| Package height (mm) | 80         |
| Package width (mm)  | 100        |
| Package length (mm) | 245        |
| IP internal         | 65         |
| Drive Over          | No         |

### Download

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



## Schematic light drawing



## Photometric

|                    |                  |
|--------------------|------------------|
| Lighting type      | Direct, Indirect |
| Light distribution | Asymmetric       |
| CCT (K)            | 3000             |
| CRI>               | 80               |
| Extreme cut off    | No               |

## Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



## Accessories & Power Supply



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)