

FLOS

03.6262.14.9V Black

Mini Glo-Ball S 0-10V Dimmable

Designed by FLOS Architectural, 2015

LED - Power LED - 3.5W - 258lm - 2700K - CRI> 80

General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	3.5
System power (W)	3.8
Source flux (lm)	358
System flux (lm)	258
Efficacy (lm/W)	67.89

Physical

Color	Black
Trim	No
Orientation	Fixed
Length (in)	5.12
Net weight (lb)	0.88
IP internal	20
IP external	20



Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B10 > 50.000h
Extreme cut off	No

Electrical

Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming range (%)	10-100

Notes

Maximum 14 spots for a single driver. For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.