

FLOS

03.6305.14C90 Black


Multi Spot 4 On Board Dimmer

Designed by FLOS Architectural, 2016



LED - Power LED - 10W - 630lm - 2700K - CRI> 90 - Beam° 11

4 accent Spot LED module can be rapidly exchanged and repositioned without tools. Light elements are quick to position and connect automatically with magnets. Built-in dimming knob dims fixture (from 20-100%), DALI and 0-10V (from 10-100%). Standard beam spread is 14° additional interchangeable lenses available in 20° and 30°, and elliptical beam spread.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	10
System power (W)	11.3
Source flux (lm)	878
System flux (lm)	630
Efficacy (lm/W)	55.75

Physical

Color	Black
Orientation	Fixed
Length (in)	4.7
Net weight (lb)	0.77
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmer on board
Dimming range (%)	20-100
Dimming interface	Dimmer Integrated

Accessories & Power Supply



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8759.00

Elliptical lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8760.00

Frosted Medium lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8761.00

Frosted Flood lens