

## Multi Spot Mini

Designed by FLOS Architectural, 2025



LED - Power LED - 6.1W - 433lm - 2700K - CRI> 90 - Beam° 19

LED lighting module with 12 spotlights and low glare, to be installed in The Glowing Track & The Zero Track Pro System.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 6.1                 |
| System power (W)       | 6.5                 |
| Source flux (lm)       | 662                 |
| System flux (lm)       | 433                 |
| Efficacy (lm/W)        | 67                  |

### Physical

|             |       |
|-------------|-------|
| Color       | White |
| Orientation | Fixed |
| IP internal | 20    |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files

|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings


|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 2700                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 91                    |
| Rg gamut index           | 100                   |
| LED Life / Failure Ratio | L90B50>59.000h_Tc85°C |
| Beam angle C0-180 (°)    | 19                    |
| Beam angle C90-270 (°)   | 19                    |
| Extreme cut off          | Yes                   |
| UGRL                     | <10                   |

Electrical

|                  |              |
|------------------|--------------|
| Insulation class | III          |
| Frequency (Hz)   | 0            |
| LED current (mA) | 150          |
| Driver           | Remote       |
| Dimmable         | No           |
| Dimming type     | Non Dimmable |
| Batteries inside | No           |