

Multi Spot Mini Casambi Integrated

Designed by FLOS Architectural, 2024



444lm - 3000K - CRI> 90 - Beam° 31

LED lighting module with 14 spotlights and low glare, to be installed in The Infra-Structure system. For wireless lighting control, choose integrated Casambi versions.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	7
Source flux (lm)	629
Lumen Output (lm)	444
Efficacy (lm/W)	64

Physical

Colour	White
Field cuttable	No
Orientation	Fixed
Length (mm)	225
Net weight (kg)	0.11
Package height (mm)	67
Package width (mm)	255
Package length (mm)	70
IP internal	20



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	31
Beam angle C90-270 (°)	31
Extreme cut off	Yes
UGRL	<16

Electrical

Insulation class	III
Main voltage (Vac)	48
Forward voltage (V)	48
LED current (mA)	150
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)