

Multi Spot Mini Dimmable Dali

Designed by FLOS Architectural, 2025



LED - Power LED - 6.1W - 433lm - 2700K - CRI> 90 - Beam° 19

LED lighting module with 12 spotlights and low glare, to be installed in The Glowing Track & The Zero Track Pro System.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6.1
System power (W)	6.5
Source flux (lm)	662
System flux (lm)	433
Efficacy (lm/W)	67

Physical

Color	Black
Orientation	Fixed
IP internal	20

Download

Family spec sheet	ZIP
Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	-----

Technical Drawings


2D	ZIP
3D	ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	91
Rg gamut index	100
LED Life / Failure Ratio	L90B50>59.000h_Tc85°C
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19
Extreme cut off	Yes
UGRL	<10

Electrical

Insulation class	III
Frequency (Hz)	0
LED current (mA)	150
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No