

My Circuit Dome

Designed by Michael Anastassiades, 2023



40W - 2268lm - 3000K - CRI> 90 - Beam° 110

Suspended luminaire for installation in the My Circuit system. Diffused downlight emission. Adjustable suspension height. Casambi version for wireless control.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	40
Source flux (lm)	3700
Lumen Output (lm)	2268
Efficacy (lm/W)	58

Physical

Colour	White
Orientation	Fixed
Length (mm)	500
Cord colour	White
Cord length (mm)	Max 3000
Net weight (kg)	0.2
IP internal	20



Download

Mounting instructions [Download PDF](#)

Photometric Files


LDT / IES [Download ZIP](#)


Technical Drawings

2D [Download ZIP](#)
3D [Download ZIP](#)




Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

Schematic light drawing




Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	91
Rg gamut index	92
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110

Electrical

Insulation class	III
Forward voltage (V)	48
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply



OPTIONAL
Control interface

ACCESSORYTYPE1

08.0824.14

Dimming Interface 1-10V to
CASAMBI