

My Circuit Spot Ø35

Designed by Michael Anastassiades, 2023



LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	8
Source flux (lm)	641
System flux (lm)	548

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Transversal tilting (°)	90
Net weight (lb)	1
Gross weight (lb)	1.77
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files


- LDT / IES [ZIP](#)

Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	91
Rg gamut index	100
LED Life / Failure Ratio	L70B50>45.000h_Tc85°C
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	200
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable

Notes

Ask us about bespoke track connector arm lengths.