

FLOS

05.5315.ERA1V Brushed Steel

My Spot Ø25 Long 1-10V Dimmable

Designed by FLOS Architectural, 2024




LED - Power LED - 4.9W - 244lm - 3000K - CRI> 90 - Beam° 11

LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 4.9 |
| Source flux (lm) | 326 |
| Lumen Output (lm) | 244 |

Physical

| | |
|--------------------------|---------------|
| Colour | Brushed Steel |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Length (mm) | 25 |
| Net weight (kg) | 0.2 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

Schematic light drawing



Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 90 |
| Rg gamut index | 101 |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°) | 11 |
| Beam angle C90-270 (°) | 11 |
| Extreme cut off | Yes |
| UGR _L | <10 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| LED current (mA) | 900 |
| Power supply | Remote |
| Dimmable | Yes |
| Power supply type | Dimmable 1-10V |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |