

My Spot Ø25 Long Non Dimmable

Designed by FLOS Architectural, 2024




LED - Power LED - 4.9W - 222lm - 2700K - CRI> 90 - Beam° 11

LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	4.9
Source flux (lm)	297
System flux (lm)	222

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20

Download

- Family spec sheet
- ↓ ZIP
- Mounting instructions
- ↓ PDF

Photometric Files


- LDT / IES
- ↓ ZIP

Technical Drawings



- 2D
- ↓ ZIP
- 3D
- ↓ ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	90
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	900
Driver	Remote
Dimmable	No
Dimming type	Non Dimmable
Batteries inside	No