

# FLOS

05.5315.ESA Brushed Bronze

## My Spot Ø25 Long Non Dimmable

Designed by FLOS Architectural, 2024



LED - Power LED - 4.9W - 244lm - 3000K - CRI> 90 - Beam° 11

LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	4.9
Source flux (lm)	326
Lumen Output (lm)	244

### Physical

Colour	Brushed Bronze
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (mm)	25
Net weight (kg)	0.2
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




### Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

## Schematic light drawing



h(m)	E(lx)	D(m)
1	4898	0.19
2	1225	0.37
3	544	0.56
4	306	0.75
5	196	0.93

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	90
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	Yes
UGR <sub>L</sub>	<10

## Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	900
Power supply	Remote
Dimmable	No
Power supply type	Non Dimmable
Batteries inside	No