

## My Spot Ø25 Long Recessed

Designed by FLOS Architectural, 2024



LED - Power LED - 2.5W - 203lm - 2700K - CRI> 90 - Beam° 11

LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Recessed            |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 2.5                 |
| Source flux (lm)       | 271                 |
| Lumen Output (lm)      | 203                 |

### Physical

|                          |       |
|--------------------------|-------|
| Colour                   | Black |
| Rotation (°)             | 360   |
| Longitudinal tilting (°) | 90    |
| Net weight (kg)          | 0.42  |
| IP internal              | 20    |
| IP external              | 20    |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP

### Technical Drawings


2D  ZIP

2D  ZIP

3D  ZIP

3D  ZIP


### Ecodesign and Energy Labelling



Non-replaceable light source



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 11        |
| Beam angle C90-270 (°) | 11        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 3                                     |
| LED current (mA)    | 800                                   |
| Power supply        | Remote                                |
| Dimmable            | Yes                                   |
| Power supply type   | Dimmable                              |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Batteries inside    | No                                    |

Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9208

Continuous current power supply of 13-20W - Dim 1-10V&Push - 110/240V - 50/60Hz with power current selected through adjustable



REQUIRED  
Power supply

Electrical

60.7773

Constant current power supply 28W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.4W / 150mA - 7.9W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.5W / 350mA - 18W / 400mA - 20.4W / 450mA - 23W / 500mA - 25.8W / 550mA - 28.4W...



REQUIRED  
Power supply

Electrical

60.7774

Constant current power supply 20W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.8W / 150mA - 8.3W / 200mA - 10.8W / 250mA - 13.2W / 300mA - 15.6W / 350mA - 18.1W / 400mA - 20.6W / 450mA - 23W / 500mA - 22.9W / 550mA - 2...



REQUIRED  
Power supply

Electrical

60.9467

Mains dimming 20W Constant current power supply, AC phase-cut adjustable, trailing & leading edge dimming, 220/240V - 50/60Hz, with dip-switch programmable power supply current. Output current: 900mA - 20W / 850mA - 20W / 800mA - 20W / 750mA - 20W / 70...



REQUIRED  
Power supply

Electrical

60.7785

Constant current power supply 42W, 220-240V CASAMBI dimmable.